

SL.NO	ITEM NAME	SPECIFICATIONS	QTY	
1	MOVING COIL AMMETERS	Accuracy: Class1.0 (1% of full scale value)between10% & 100% of scale Scale Length : 140mm approx. Test Voltage : 200V AC(r m s) for 1 minute Insulation Resistance : Over 20 Mega Ohms at 500V DC Sensitivity : 1000 Ohms / Volt Knife edge pointer & Anti – parallax mirror scale Shock resistant Pivot jewel movement Tough Bakelite case Dust proof Minimum internal heating, Quick response	0 - 50 - 100 Micro Amps	13
			0 - 250 - 500 Micro Amps	10
			0-25-50 mA	3
			0-50-100 mA	10
			0 - 1 - 2 AMPS	10
			0 - 250 mA - 500 mA	10
2	MOVING COIL VOLTMETER	Accuracy: Class1.0 (1% of full scale value)between10% & 100% of scale Scale Length : 140mm approx. Test Voltage : 200V AC(r m s) for 1 minute Insulation Resistance : Over 20 Mega Ohms at 500V DC Sensitivity : 1000 Ohms / Volt Knife edge pointer & Anti – parallax mirror scale Shock resistant Pivot jewel movement Tough Bakelite case Dust proof Minimum internal heating, Quick response	0 - 5 - 10 V	10
			0 - 15 - 30 V	10
			0- 50 - 100 V	10
3	Portable and Educational Desk model VOLTMETER	Type - Moving Iron,Current Range- 0-5A,Accuracy-1.0,Temperature - 27 Degree Celcius,	2	
4	Portable and Educational Desk model AMMETER	Type - Moving Iron,Current Range- 0-5A,Accuracy-1.0,Temperature - 27 Degree Celcius,	2	



*Ambar*  
*celius may smart*  
*1000 AEE*

5	<b>Portable and Educational Desk model WATTMETER</b>	Voltage Rating- 250V/500V,Current Rating- 5A/10A,Single Phase,Accuracy-1.0,Insulation Resistance-20MEGA OHM,Tempareature- 27 Degree Celcius		2
6	<b>ENERGY METER</b>	Single Phase,240V,50Hz,10-20A,600Rev/Kwh		6
7	<b>Digital Multimeter</b>	3 ¾ Digit Display with 4000 count,DC-1000V, Auto and manual range selection,AC-750V,Current-10A,Auto power off. Temperature measurement up to 750 degree Celsius, Frequency measurement up to 10MHz,Capacitance measurement		18



*Amichu  
 Celius May shant  
 (NO D AES)*